



Parts & Materials

No.	Description	Pressure	Material		
			P134/135	P234/235	P334/335
1	Body	ALL	A105	*CF8M	LF2
2	End Caps	ALL	A105	CF8M	LF2
3	Seats	2000	TFM4215	TFM4215	TFM4215
		3000/4000	Delrin®	Delrin®	Delrin®
		6000	Peek™ + 15% C.F.	—	Peek™ + 15% C.F.
4	Ball	2000	CF8M	CF8M	CF8M
		3000/4000			
		6000	17-4PH	—	17-4PH
5	Stem	2000/3000	17-4PH	17-4PH	17-4PH
		4000/6000			
6	Body O-Ring	ALL	HSN (HNBR)	HSN (HNBR)	HSN (HNBR)
7	Thrust Washer	2000	PTFE + 15% G.F.	PTFE + 15% G.F.	PTFE + 15% G.F.
		3000/4000	Delrin®	Delrin®	Delrin®
		6000	Peek™ + 15% C.F.	—	Peek™ + 15% C.F.
8	Packing	ALL	PTFE + 15% G.F.	PTFE + 15% G.F.	PTFE + 15% G.F.
		6000	Graphite	—	Graphite
9	Packing Follower	ALL	304	304	304
10	Gland Flange	ALL	CS Plated	CS Plated	CS Plated
11	Handle	ALL	CS Plated	CS Plated	CS Plated
12	Self Locking Nut	ALL	CS Plated	CS Plated	CS Plated
13	Belleville Washer	ALL	Stainless Steel	Stainless Steel	Stainless Steel
14	Stop Screw	ALL	Stainless Steel	Stainless Steel	Stainless Steel
15	Stem O-Ring	ALL	HSN (HNBR)	HSN (HNBR)	HSN (HNBR)
16	Body Gasket	ALL	Graphite	Graphite	Graphite

Note: We reserve the right to change materials and specifications. Item 8 & 15: Firesafe Design
 *CF8M Max Pressure 3000 psi